

CMI-CMMPP10040LL-SERIES



Features


- ▶ High current and low profile.
- ▶ Metal powder molding type for EMC protection.
- ▶ Available tape and reel for auto insertion.
- ▶ RoHS compliant

Applications

- ▶ For DC/DC converter(LED/OLED TV, TABLAT, DISPLAY, GRAPHIC CARD, NOTE PC, SETTOP, etc.)
- ▶ Equipment using for automobiles (ECM, airbags, headlights, electronic Powder steering, motors, ABS, other)




Dimension (Unit:mm)



A	B	H
10.85±0.5	10.0±0.4	4.0 Max

Land Pattern (Unit:mm)



L	G	H
13.6	5.4	4.1

Specifications

Part Number	Inductance (uH) ±20%	DCR(mohm) Max(Typ)	IDC1(A) Max(Typ)	IDC2(A) Max(Typ)	Test Frequency (Hz)
CMI-CMMPP10040LL-R78M	0.78	1.9(1.8)	28.00(32.00)	19.00(21.00)	1M
CMI-CMMPP10040LL-1R0M	1.0	3.2(2.6)	25.00(28.00)	14.20(15.80)	1M
CMI-CMMPP10040LL-2R2M	2.2	9.6(8.0)	22.00(24.00)	14.00(15.00)	1M
CMI-CMMPP10040LL-4R7M	4.7	15.0(12.5)	16.00(17.00)	12.00(13.00)	1M
CMI-CMMPP10040LL-6R8M	6.8	19.2(16.0)	13.50(14.50)	9.00(9.50)	1M
CMI-CMMPP10040LL-100M	10	31.2(26.0)	9.50(10.50)	7.00(7.50)	1M
CMI-CMMPP10040LL-150M	15	48.0(40.0)	9.00(10.00)	6.00(6.50)	1M
CMI-CMMPP10040LL-220M	22	57.6(48.0)	7.50(8.00)	5.80(6.20)	1M

- IDC1: When based on the inductance change rate (approximately 30% below in the initial value)
- IDC2: When based on the temperature increase (Temperature increase of approximately 40°C by self heating)
- Operating Temperature Range(including self temperature) : -40°C ~ +165 °C

Ilson Sales Office (KOREA)
 H.K Sales Office (HongKong)
 Shenzhen Sales Office (CHINA)
 LA Sales Office (USA)
 Hungary Sales office (EUROPE)

+82)31-904-1444
 +852)2711-5551
 +0755-8663-6929
 +1)866-446-3586
 +36)30-521-7818

coilmaster@coilmaster.com
coilmaster@coilmaster.com
kimha@coilmaster.com
markyang@coilmaster.com
coilmaster@coilmaster.com

- All specifications are subject to change without notice.
- Update date : 2017.11.03

www.coilmaster.com