

CMI-CMMPP6020LH-SERIES



Features


- ▶ High current and low profile.
- ▶ Metal powder molding type for EMC protection.
- ▶ Available tape and reel for auto insertion.
- ▶ Halogen-Free
- ▶ RoHS compliant
- ▶ AEC-Q200 qualified.

Applications

- ▶ Equipment using for automobiles (ECM, airbags, headlights, electronic Powder steering, motors, ABS, other)




Dimension (Unit:mm)



A	B	H
6.0±0.35	6.0±0.25	2.0 Max

Land Pattern (Unit:mm)



L	G	H
6.2	2.8	4.2

Specifications

Part Number	Inductance (uH) ±20%	DCR(mohm) Max(Typ)	IDC1(A) Max(Typ)	IDC2(A) Max(Typ)	Test Frequency (Hz)
CMI-CMMPP6020LH-1R0M	1.0	30.0(25.0)	14.00(16.00)	5.20(5.60)	1M
CMI-CMMPP6020LH-2R2M	2.2	51.6(43.0)	12.00(13.00)	4.20(4.40)	1M
CMI-CMMPP6020LH-3R3M	3.3	72.0(60.0)	9.50(11.00)	3.60(3.80)	1M
CMI-CMMPP6020LH-4R7M	4.7	108.0(90.0)	7.00(8.00)	3.00(3.20)	1M
CMI-CMMPP6020LH-6R8M	6.8	150.0(125.0)	6.50(7.50)	2.70(2.90)	1M
CMI-CMMPP6020LH-100M	10	216.0(180.0)	5.00(5.50)	2.50(2.70)	1M

- IDC1: When based on the inductance change rate (approximately 30% below in the initial value)
- IDC2: When based on the temperature increase (Temperature increase of approximately 40°C by self heating)
- Operating Temperature Range(including self temperature) : -40°C ~ +165 °C

Ilsan Sales Office (KOREA) +82)31-904-1444
 Shenzhen Sales Office (CHINA) +86)755-8663-6929
 Hungary Sales office (EUROPE) +36)30-913-7706

H.K Sales Office (HONGKONG) +852)2711-5551
 LA Sales Office (USA) +1)866-446-3586

• You can also contact us by e-mail : coilmaster@coilmaster.com

- All specifications are subject to change without notice.
- Update date : 2018.10.25

www.coilmaster.com