

CMI-CMMPP6024LH-N SERIES



Features


- ▶ High current and low profile.
- ▶ Metal powder molding type for EMC protection.
- ▶ Available tape and reel for auto insertion.
- ▶ RoHS compliant
- ▶ AEC-Q200 qualified.
- ▶ Halogen-Free

Applications

- ▶ Equipment using for automobiles (ECM, airbags, headlights, electronic Powder steering, motors, ABS, other)




Dimension (Unit:mm)



A	B	H
6.95±0.35	6.6±0.25	2.4 Max

Land Pattern (Unit:mm)



L	G	H
8.4	3.7	3.5

Specifications

Part Number	Inductance (uH) ±20%	DCR(mohm) Max(Typ)	IDC1(A) Max(Typ)	IDC2(A) Max(Typ)	Test Frequency (Hz)
CMI-CMMPP6024LH-1R0M-N	1.0	15.0(12.5)	20.00(22.00)	9.00(10.00)	1M
CMI-CMMPP6024LH-6R8M-N	6.8	72.0(60.0)	7.00(8.00)	3.70(3.90)	1M
CMI-CMMPP6024LH-100M-N	10	96.0(80.0)	5.50(6.00)	3.50(3.70)	1M

- IDC1: When based on the inductance change rate (approximately 30% below in the initial value)
- IDC2: When based on the temperature increase (Temperature increase of approximately 40°C by self heating)
- Operating Temperature Range(including self temperature) : -40°C ~ +165 °C

Ilisan Sales Office (KOREA) +82)31-904-1444
 Shenzhen Sales Office (CHINA) +86)755-8663-6929
 Hungary Sales office (EUROPE) +36)30-913-7706

H.K Sales Office (HONGKONG) +852)2711-5551
 LA Sales Office (USA) +1)866-446-3586

• You can also contact us by e-mail : coilmaster@coilmaster.com

- All specifications are subject to change without notice
- Update date : 2017.11.03

www.coilmaster.com