

CMI-CTLF4420V-SERIES




Features


- ▶ Hearing Aid Compatibility/Telecoil-antennas
- ▶ Realizes small size and low profile
- ▶ 100% Lead(Pb) & Halogen-Free and RoHS compliant.
- ▶ High reliability -Reliability test meet AEC-Q200

Applications

- ▶ Decoupling in RF and IF-circuit/Transponder antenna




Dimension (Unit:mm)



A	B	C	D
4.55±0.25	2.2±0.25	2.0±0.2	0.98 ref

Land Pattern (Unit:mm)



L	G	H
4.60	2.54	2.00

Specifications

Part Number	Inductance (uH)	Tolerance (±)	SRF MHz(min.)	DCR(Ω) Max.	IDC1(mA) Max.
CMI-CTLF4420V-352K	3500	10	1.00	85	20
CMI-CTLF4420V-352K	4900	10	0.65	109	20

- Inductance Tested at 125kHz, 1Vrms(20 °c)
- IDC1: When based on the inductance change rate (approximately 30% below in the initial value)
- Operating Temperature Range(including self temperature) : -40°c ~ +125 °c

Ilsan Sales Office (KOREA) +82)31-904-1444
 Shenzhen Sales Office (CHINA) +86)755-8663-6929
 Hungary Sales office (EUROPE) +36)30-913-7706

H.K Sales Office (HONGKONG) +852)2711-5551
 LA Sales Office (USA) +1)866-446-3586

▪ You can also contact us by e-mail : coilmaster@coilmaster.com

- All specifications are subject to change without notice.
- Update date : 2016.04.22